

The Double Roman

HIGH QUALITY CONCRETE



FINISH
TOP ONE

The RDUK Double Roman sets a new standard for these tiles which everyone from Architects to Roofers appreciate..

The Double Roman is superbly crafted with its classic, timeless shape and the design is perfectly enhanced by the rounded trimmed edge to enhance the finished roof.

With a covering capacity of just 9.7 tiles per square metre it also makes the Double Roman the perfect choice for a very economical and attractive roof. These Double Roman tiles are engineered to the highest of standards and are available in six different colours with silk coatings and benefit from a wide range of fittings.

RDUK
ROOFING DISTRIBUTION UK

Order your **FREE** roof tile sample email: samples@roofingdistributionuk.com

 01375 397 140  sales@roofingdistribution.com  roofingdistributionuk.com

The Double Roman Concrete Tile

A long established Roman design popular in most regions, ideal for any type of project.



Double Roman technical details

Length:	420mm
Width:	332mm
Gauge:	310 - 345mm
Headlap (min):	75mm (22.5°+), 100mm (17.5°+), 110mm (15°+)
Cover width (mm):	300mm ± 2.0
Minimum roof pitch*:	15° @110mm headlap
Number of tiles per m ² (min):	9.7
Weight per tile:	4.4 kg
Weight per m ² (min):	44 kg
Battens per m ² (min):	3 - 3.2
Batten size (mm):	50 x 25 - 600mm centres
Fixings clips:	Eaves and tile clips
Nails - ring shank aluminium alloy:	45 x 3.35mm
Screw - with neoprene washer seal:	45 x 4.5mm

Please Note: Fixing specs may vary due to roof pitch and location

Double Roman range available in 6 colours



- ▶ Superior Quality Double Pantile ▶ Eco friendly Top One finish
- ▶ Cleaner, Smooth Round Trimmed Edges ▶ Only 9.7 tiles per m²
- ▶ Range of Colours & Quality Fittings

Manufactured to comply with the performance standards of EN490/491 and DIN Plus



Low Pitch Roof Specification 17° - 15°

- Lay Double Roman straight bond.
- Headlap minimum 110mm.
- Use appropriate air and vapour permeable underlay, which does not require secondary roof ventilation.
- Lay the roof underlay to the manufacturer's instructions.
- Maximum rafter length 7.5m.
- All tiles to be clipped with RDUK purpose made tile clips, reference 409/001. Do not nail the tiles at 17° and below.
- Roof perimeters including, abutments and around roof windows must be securely fixed to BS 5534.

Double Roman tile fittings



FOR MORE FITTINGS VISIT OUR WEBSITE

For more information on our **Concrete** tiles or to order a **FREE** sample call us on **01375 397 140**

☎ 01375 397 140 ✉ sales@roofingdistribution.com 🌐 roofingdistributionuk.com

RDUK
ROOFING DISTRIBUTION UK