

Declaration of Performance

Unique identification code of the product-type:	VIANA 50x25
Type, batch or serial number or any other element	
allowing identification of construction product as	500x250mm, Quarry A Baña, Leon, Spain
required under Article 11(4):	
Intended use or uses of the construction product in	
accordance with the applicable harmonized	Slate and carbonate slate for discontinuous roofing and
Technical Specification, as foreseen by the	cladding
manufacturer:	
Name, registered trade name or registered trade	
mark and contract address of the manufacturer as	GAELIC PIZARRAS, S.L.
required under Article 11(5):	
Where applicable, name and contact address of the	
authorized representative whose mandate covers the	N/A
tasks specified in Article 12(2):	
System or systems of assessment and vertification of	
constancy of performance of the construction product	AVCP System 4
as set out in CPR, Annex V:	
Declared Performance:	
Dimmensional Tolerances	
Individual thickness and variation to nominal:	4,5 mm ± 35%
Deviation from declared length and width:	Complies
Deviation from edge straightness:	Complies
Deviation from squareness:	Complies
Strength (Characteristic Modulus of rupture):	Transverse: 30,0 N/mm² Longitudinal: 66,0 N/mm²
Performance:	
Water absorption:	0,25% W1
Freeze-thaw cycling:	Not required
Thermal cycling:	T1
Sulfur dioxide exposure:	S1
Non-carbonate carbon content:	0,5% . Complies (≦2%)
Carbonate content:	1,5%. Complies
	None in conditions of use as roofing or external
Release of dangerous substances:	cladding
External fire performance:	Deemed to satisfy
Reaction to fire:	Deemed to satisfy A1

8. Performance of the product identified in Points 1 and 2 is in conformity with the declared performance in point 7.

9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in Point 4.

Signed for and on behalf of the manufacturer by:

Emilio Prada Garcia, Managing Director Date of Issue: 02/01/2024