

CREST NELSKAMP ROOFING TILES

H15 clay pantile



H15 Natural Red



crest
NELSKAMP
ROOFING TILES

t: 01430 432667

www.crest-bst.co.uk

f: 01430 433000

e: info@crest-bst.co.uk

Manufactured to comply with the requirements of EN1304 European Standard for Clay Roof Tiles

H15 Interlocking Clay Pantile

▶ High quality clay tiles ▶ Minimum roof pitch 15° ▶ Economical ▶ Only 14.6 tiles per m²

H15 Technical details:

| | |
|----------------------------------|------------|
| Length | 410 mm |
| Width | 260 mm |
| Gauge | 322-342 mm |
| Cov' Width (mm) | 200 ± 2.0 |
| Min' roof pitch* | 15° |
| No. of tiles per m ² | 14.6 |
| Weight per tile | 3.2 kg |
| Weight per m ² (min.) | 46.72 kg |
| Battens per m ² (min) | 2.9 |
| Batten size (mm) | 50 x 25 |
| Fixing | Clipped |

Fittings Include:

H15 Half round ridge (2.4 per m)



H15 Half round interlocking ridge (3.0 per m)



H15 Starter ridge tile



H15 End ridge tile



H15 Cloaked verge tiles (left and right hand)



H15 Double roll tile

The H15 range of colours and fittings

H15 Natural Red (115)



H15 Red (116)



H15 Toscana (152)



H15 Slate Grey (119)



H15 Matt Black (133)



H15 Blue Reduced (144)



To overcome any minor shade variations inherent in the production of natural clay products, we recommend that tiles are mixed from at least 3 pallets on site. The colours shown here are only as accurate as allowed for by the printing process. Product samples are available on request.

crest
NELSKAMP
ROOFING TILES



For more information on the H15 or to order a sample call us on **01430 432667**