

| Declaration of Performance | | |
|---|--|--|
| 026-00 | | |
| Clay roof tiles and fittings | | |
| Tiles F15 – OH16 Wolds – H15 | | |
| For roof coverings on inclined roofs as well as outer wall claddings | | |
| Dachziegelwerke Nelskamp GmbH Waldweg 6 46514 Schermbeck | | |
| Not applicable | | |
| System 4 | | |
| Not applicable | | |
| Not applicable | | |
| Main features | Performance | Harmonised technical specification |
| Mechanical strength | Passed | EN 1304 (for edition of applicable standard, see front) |
| Performance under stress from external fire | B _{ROOF} No test | |
| Fire performance | Category A1 to F | |
| Water impermeability | Fulfils Performance level 1 Test procedure 1 Test procedure 2 | |
| Dimensions and variations in dimension | Passed | |
| Durability (Frost resistance) | Fulfils Test procedure E Performance level 1 (150 cycles) | |

The performance of the product as per numbers 1 and 2 corresponds with the declared performance in accordance with number 9.

The responsibility for compiling this Declaration of Performance lies solely with the manufacturer as per number 4.

Signed for the manufacturer and in the name of the manufacturer by:

Schermbeck, 25.04.13


Dipl.-Ing. Manfred Bracht,
Managing Director

| | |
|---|---|
|  | |
| Dachziegelwerke Nelskamp GmbH Waldweg 6 46514 Schermbeck | |
| 2013 | |
| Clay roof tiles and fittings | |
| EN 1304 (see front) | |
| 026-00 | |
| Clay roof tiles and fittings for roof coverings and outer wall claddings | |
| Mechanical strength | Passed |
| Performance under load from external fire | B _{ROOF} No test |
| Fire performance | Category A1 to F |
| Water impermeability | Fulfils Performance level 1 Test procedure 2 |
| Dimensions and variations in dimension | Passed |
| Durability (Frost resistance) | Fulfils Test procedure E Performance level (150 cycles) |