

G10 FLAT CLAY ROOF TILE

HIGH QUALITY CLAY TILES FOR EVERY
PROJECT INCLUDING LOW PITCH



The G10 Flat Clay Roofing Tile is a large format **double interlocking** flat clay tile that is available in a range of colours, finishes and fittings.

G10
BLACK
GLOSS
(218)

THE G10 LARGE FORMAT CLAY TILE

G10
RED
BROWN
(202)



G10
SLATE
GREY
(225)



These tiles are superbly engineered and designed for a quick, easy and secure installation and are ideal for use with low pitch roofs. The G10 can also be used for vertical cladding on walls and façade.

With a covering capacity of only 10 tiles per square metre, this allows the G10 Flat Clay Roofing Tile to be installed very economically. The G10 is an ideal tile for low pitch roofs and can even be used as a cost effective alternative to vertical cladding systems. Like all RDUK tiles the G10 flat clay roofing tile is available with a wide range of fittings.

- > **High quality clay tile**
- > **Minimum roof pitch 10°**
- > **Long term durability**
- > **Eco friendly**
- > **Low maintenance**
- > **Wide range of colours & fittings**
- > **Only 10 tiles per m²**
- > **Quick, easy & secure installation**

Whatever your needs, from traditional rustic pantiles to beautiful large format clay tiles and crafted glazed tiles, we have a wide choice of roofing materials all proven to compliment any type of project.

Throughout this brochure on the G10 you should find most of the details you need, however if you require more information on this or any other product please don't hesitate to call us on 01375 397 140.

LARGE FORMAT DOUBLE INTERLOCKING . . .

TECHNICAL DATA

Length ~ 486 mm.

Width ~ 296 mm.

Gauge ~ 384 mm to 404 mm.

Covering Width ~ 250 mm ± 1.0 mm.

Minimum low roof pitch ~ 10°

Number of tiles per m² ~ 10.

Weight per tile ~ 4.6 kg.

Weight per m² (min.) ~ 45.54 kg.

Battens required per m² (min) ~ 2.5

Batten size (mm) ~ 50 x 25

Fixing ~ Clipped



LOW PITCHES 17°-10°

- > Use appropriate air and vapour permeable underlay, which does not require secondary roof ventilation.
- > Lay the roof underlay to the manufacturer's instructions.
- > Lay G10 tiles broken bond.
- > Headlap minimum 100mm.
- > Maximum rafter length 6m.
- > All tiles are to be clipped with purpose-made tile clips, reference 409/215
- > Left Hand Verge tiles are to be fixed with 45mm tile fixing screw with a neoprene washer, also fix verge clips if mortar bedding the verge.
- > Roof perimeters including around roof windows must be securely fixed to BS 5534.

COLOUR AVAILABILITY

G10 range of colours and finishes.



Natural Red (201)



Red Brown (202)




Slate Grey (225)



Black Gloss (218)



Matt Black (239)



Black Engobe (232)

Colour deviations:

Our clay roofing tiles are environment-friendly building materials. When using natural raw materials you may experience colour deviations. This is often the case with naturally red tiles since the fired colour is the sole result of natural raw materials with no added metal oxides to change the colour.

Deviations are also possible in the colours for reasons and limitations relating to printing methods. Clay roof tile surfaces: Minor impairments to the surface are possible due to transport or site handling. This does not effect the overall quality or performance of the tiles. (Jan 2024)



Technical Support



Need help with your roof?
Please contact our team of experienced professionals.

Customer Service



Telephone: 01375 397 140
Opening times:
Mon - Fri: 8.00am to 5.00pm

Nelskamp Guarantee




Complete peace of mind
with our 30 year guarantee
Ask for details.

G10 ACCESSORIES


CLAY FITTINGS, RIDGES AND SPECIAL TILES

RDUK Nelskamp manufacture a wide selection of clay roof tile fittings and accessories.
The G10 special tiles are available in a selection of colours designed to match your roof.
For further details please call us on 01375 397 140.

STANDARD TILES AND VERGE TILE FITTINGS



RIDGE AND HIP TILES



SPECIAL TILES



FIXINGS



DRY FIX SYSTEM



Necoroll dry fix system for ridge and hip

Faster, cleaner, more effective solutions for all roofs.

The highest quality aluminium ridge roll using the latest micro-ventilation technology. Provides excellent protection and ridge and ridge ventilation.

☎ 01375 397 140

✉ sales@roofingdistribution.com

🌐 roofingdistributionuk.com



Creative Roofscaping

For more information on our roofing tiles or to order a FREE tile sample contact the RDUK team today.

roofingdistributionuk.com