G10 PRO SMOOTH FLAT CLAY ROOF TILE

HIGH QUALITY CLAY TILES FOR EVERY PROJECT INCLUDING LOW PITCH



The G10 Pro Flat Clay Roofing Tile is a large format **double interlocking** flat clay tile that is available in a range of colours, finishes and fittings.



G10 PRO
BLACK
ENGOBE

roofingdistributionuk.com

RDUK
ROOFING DISTRIBUTION UK

THE G10 PRO LARGE FORMAT CLAY TILE

G10
PRO
NATURAL
RED



G10
PRO
MATT
BLACK

These tiles are superbly engineered and designed for a quick, easy and secure installation and are ideal for use with low pitch roofs. The G10 Pro can also be used for vertical cladding on walls and façade.

With a covering capacity of only 10 tiles per square metre, this allows the G10 Pro Flat Clay Roofing Tile to be installed very economically. The G10 Pro is an ideal tile for low pitch roofs and can even be used as a cost effective alternative to vertical cladding systems. Like all RDUK tiles the G10 Pro flat clay roofing tile is available with a wide range of fittings.

- **High quality clay tile**
- **Minimum roof pitch 10°**
- **Long term durability**
- **Eco friendly**
- **Low maintenance**
- **Wide range of colours & fittings**
- **Only 10 tiles per m²**
- **Quick, easy & secure installation**

Whatever your needs, from traditional rustic pantiles to beautiful large format clay tiles and crafted glazed tiles, we have a wide choice of roofing materials all proven to compliment any type of project.

Throughout this brochure on the G10 Pro you should find most of the details you need, however if you require more information on this or any other product please don't hesitate to call us on 01375 397 140.

LARGE FORMAT DOUBLE INTERLOCKING . . .

TECHNICAL DATA

Length ~ 488 mm.
Width ~ 297 mm.
Gauge ~ 386 mm to 406 mm.
Covering Width ~ 250 mm ±1.0 mm.
Minimum low roof pitch ~ 10°
Number of tiles per m² ~ 9.9 - 10.4 pcs
Weight per tile ~ 4.5 kg.
Weight per m² (min.) ~ 44.55 kg.
Battens required per m² (min) ~ 2.5
Batten size (mm) ~ 50 x 25
Fixing ~ Clipped



LOW PITCHES 17°-10°

- Use appropriate air and vapour permeable underlay, which does not require secondary roof ventilation.
- Lay the roof underlay to the manufacturer's instructions.
- Lay G10 tiles broken bond.
- Headlap minimum 100mm.
- Maximum rafter length 6m.
- All tiles are to be clipped with purpose-made tile clips, reference 409/215
- Left Hand Verge tiles are to be fixed with 45mm tile fixing screw with a neoprene washer, also fix verge clips if mortar bedding the verge.
- Roof perimeters including around roof windows must be securely fixed to BS 5534.
- Further low pitch roofing advice available on our website.

COLOUR AVAILABILITY

G10 PRO range of colours and finishes.



Natural Red



Red Brown



Slate Grey (available on request)



Matt Black



Black Gloss



Black Engobe

Colour deviations:
Our clay roofing tiles are environment-friendly building materials. When using natural raw materials you may experience colour deviations. This is often the case with naturally red tiles since the fired colour is the sole result of natural raw materials with no added metal oxides to change the colour.
Deviations are also possible in the colours for reasons and limitations relating to printing methods. Clay roof tile surfaces: Minor impairments to the surface are possible due to transport or site handling. This does not effect the overall quality or performance of the tiles. **(Jan 2026)**

Technical Support

Need help with your roof? Please contact our team of experienced professionals.

Customer Service

Telephone: 01375 397 140
Opening times:
Mon - Fri: 8.00am to 5.00pm

Nelskamp Guarantee

Complete peace of mind with our 30 year guarantee Ask for details.

G10 PRO ACCESSORIES


CLAY FITTINGS, RIDGES AND SPECIAL TILES

RDUK Nelskamp manufacture a wide selection of clay roof tile fittings and accessories.
The G10 special tiles are available in a selection of colours designed to match your roof.
For further details please call us on 01375 397 140.

STANDARD TILES AND VERGE TILE FITTINGS



Standard Tile



Half Tile
Right hand tile




Double Roll
Left hand verge finishing tile




Half Double Roll
Left hand verge finishing tile


All sizes are approx. Tolerances according to DIN EN 1304. Covering sizes are to be determined on site. Subject to technical changes.




Left Hand Cloaked Verge



Right Hand Cloaked Verge



Half Left Hand Cloaked Verge



Half Right Hand Cloaked Verge

RIDGE AND HIP TILES



Standard Tapered Ridge
(2.7 pc/m)




Standard Starter Ridge




Standard End Ridge




Standard Hip Starter




Universal Hip Junction




Angled Ridge (2.6 pc/m)



Angled Ridge Starter




Angled Ridge End




Angled Ridge Block End


SPECIAL TILES



External Mansard
Please note mansard bespoke tiles are made to order



Internal Mansard



Mono Ridge
Verge tiles left/right are also available



Ventilation Tile
Low pitch vent tile also available for 17° to 15°

FIXINGS



Fixing Clip
No. 409/234



Ridge Clip
No. 470/41 for standard ridge tile



Universal Eave Clip
No. 436a



Verge Clip



Tile Fixing Screw
Left hand verge tiles are to be fixed with 45mm screw with neoprene washer

DRY FIX SYSTEM



Necoroll dry fix system for ridge and hip

Faster, cleaner, more effective solutions for all roofs.

The highest quality aluminium ridge roll using the latest micro-ventilation technology. Provides excellent protection and ridge and ridge ventilation.

Creative Roofscaping

For more information on our **roofing tiles** or to order a **FREE** tile sample contact the RDUK team today.

roofingdistributionuk.com

01375 397 140
sales@roofingdistribution.com
roofingdistributionuk.com

RDUK
ROOFING DISTRIBUTION UK