

UNITED-KINGDOM





DESIGN FOR A COLOURFUL LIFE





The beauty of nature in fibre cement

CEMENT SLATES

FIBRE CEMENT A MATERIAL WITH ITS OWN LANGUAGE

SVK slates are composed of a homogeneous mixture of Portland cement, selected reinforcement fibres of superior quality, additives and water.

DIMENSIONAL STABILITY

SVK slates offer structural consistency, requiring no preliminary grading before fixing. This combined with their ease of installation results in considerable savings in time and associated costs on site.

LIGHT WEIGHT

Due to their light weight, SVK slates do not require a heavy load bearing roof construction, which means less timber is required for the structure.

EASY TO HANDLE & WORK WITH

The strength and stability of SVK slates make them resistant to breakage and very easy to work with on site. SVK slates are strapped in easy to handle bundles.

MOSS INHIBITING CONSTITUENTS

In order to prevent moss growth, special moss inhibiting constituents are added to the double coating.

ENVIRONMENTALLY FRIENDLY

At SVK we take our environmental responsibilities seriously. Along with using organic fibres, SVK slates are also coated with a high-quality and durable acrylic paint, which is water-based.

3 DIFFERENT COLOURS & 4 DIFFERENT FINISHES

Choose between 4 different finishes: textured with dressed edges, smooth with dressed edges, textured with squared edges and smooth with squared edges.

Choose between 3 colours: blue-black, Welsh blue or premium black. Our wide range of ridge tiles and other accessories helps you to achieve a perfect finish to your roof.



A family business with a rich tradition and a focus on the future.





PAST

MORE THAN 110 YEARS OF **BUIL DING KNOW-HOW**

A family business with a rich tradition and a focus on the future. We currently have over 110 years of experience as a producer and distributor of construction materials. Thanks to this experience we know better than anyone how to adapt to constant evolution. Today our specialty is the production of fibre cement, a material made from a combination of reinforcing fibres, additives, cement and water.

Fibre cement is used for both roofing and façade applications. From agricultural applications involving sheets of corrugated material to unique design projects using slates and façade panels.

FUTURE

Through continuous product development we try to produce new and unique products all the time. This way, each façade and roof has its own touch.

Furthermore, ecology is an increasingly important element in the construction sector. In part thanks to our Solar Panel film we try to meet these important requirements.

MONTANA The look of natural slates with the benefits of fibre cement

SVK MONTANA

MONTANA TEXTURED

Montana Textured slates have a structured surface with dressed edges that recreate the appearance of traditional natural slates. This natural looking slate is available in an attractive blue-black and Welsh blue colour. The Welsh blue slate looks very similar to the Blue Bangor slates. The textured slate variant is available in a 600x300 mm and 600x600 mm format.

Thanks to its natural appearance, this slate has been popular on private houses and public buildings throughout Ireland and the UK. The Montana Textured slates have a multi layer acrylic based coating on both their edges and surface. This coating counteracts the growth of moss. The textured slates have a 4 mm nominal thickness.

MONTANA SMOOTH

The Montana smooth slates have a smooth surface with dressed edges. The edges also recreate a natural look of the slate. As with the textured version, the smooth variant is available in a 600x300 mm and 600x600 mm format. Nominal thickness is also 4 mm. This version is only available in the blue black colour but with the same acrylic based high quality coating as the textured slates.







FINISH

MONTANA TEXTURED

Montana textured has a textured surface with dressed edges. The coating is an acrylic high quality coating. Both edges and surface are coated and the coating counteracts the growth of moss.

MONTANA SMOOTH*

Montana smooth slates have a smooth surface with dressed edges. Same as the textured slates, the coating is an acrylic high quality coating which counteracts the growth of moss.

COLOURS





BLUE BACK

347 WELSH BLUE

* Montana Smooth slates are only available in blue black.

SIZES

All Montana slates are available in following sizes:

- 600 x 300 mm
- 600 x 600 mm

ARDONIT Slates with a more modern look

SYK ARDONIT

ARDONIT SMOOTH

Ardonit slates have a smooth surface with squared edges. Thanks to this, the slates have a more modern look. These slates have a high quality acrylic coating. The slate is available in blue-black and premium black colour. The Ardonit premium black slate has been specifically manufactured with the UK market and customer in mind.

Ardonit slates are easy to install as their dimensions are stable. Ardonit slates are made from best quality fibres only. That's why the slate is to be known as the strongest on the market.

ARDONIT TEXTURED

The Ardonit textured slates have a textured surface with a square edge. The slate has squared edges which makes it easier to place. This Ardonit slate comes close to the look of the natural slate and is available in the colour blue-black. The slates also have a nominal thickness of 4 mm and are available in the 600x300 mm and 600x600 mm format.







FINISH

ARDONIT SMOOTH

Ardonit smooth slates have a smooth surface and squared edges. The coating is an acrylic high quality coating which counteracts te growth of moss.

ARDONIT TEXTURED*

Ardonit textured slates have a textured surface with squared edges. As with the textured slates, the coating is an acrylic high quality coating which counteracts the growth of moss.

COLOURS

ARDONIT





336

BLUE-BLACK PREMIUM BLACK

* Ardonit Textured slates are only available in blue black.

SIZES

All Ardonit slates are available in following sizes:

- 600 x 300 mm
- 600 x 600 mm



SYK RIDGES

STRONGEST & MOST DURABLE RIDGES

SVK ridges are the strongest ridges on the market. No other ridge comes close to our values concerning bending strength. This is achieved because SVK is the only manufacturer who presses their ridges during production. Because we press our ridges, we achieve a much higher volume mass and bending strength.

SVK ridges are very durable. Because they are pressed, our ridges obtain a much higher density than ridges which are manually manufactured. This high density also largely diminishes the water absorption. The low water absorption rules out that our ridges would deform or suffer frost damage.

TOP QUALITY PAINT COAT

The quality of the paint coat on our ridges is unequalled. SVK has more than 70 years of experience in preparation and application of paint. This technical ability and the fact that our ridges have a very low water absorption, enables us to produce ridges with an extraordinary UV-resistance and an unequalled adhesion of the paint.

FOR EVERY PITCH THE RIGHT RIDGE

Roof pitch: 25° - ridge angle = 135° Roof pitch: 30° - ridge angle = 120° Roof pitch: 40° - ridge angle = 105° Roof pitch: 45° - ridge angle = 90°









All SVK slates are delivered on wooden pallets fully encased and shrink wrapped.

Slates are strapped in bundles for ease of use.

The SVK slates should not be allowed to become wet during storage or transport as this may cause efflorescence staining as a result of water accumulating between the surfaces of the slates. If stored outside for short periods, the hood should be removed and the slates should be covered with a vapour-open, watertight tarpaulin.



5 REASONS TO CHOOSE SVK FIBRE CEMENT SLATES



We don't bend on quality!





STRONGEST SLATES

SVK slates are the strongest slates available on the market. No other slate comes close to our values concerning bending strength. This is achieved because SVK exclusively use and source fibres of the best quality and because our fibre cement is double pressed.



EXTREMELY DURABLE

Our slates are extremely durable. The water absorption of our slates is, on average, half the value of other manufacturers. SVK is the only manufacturer who applies a double paint coat on the front side and the edges of the slates. This low water absorption enhances the durability of the slates, it is out of the question that they would suffer frost damage.



HIGH QUALITY PAINTING

The quality of the paint coat on our slates is unequalled. SVK has more than 70 years of experience in preparation and application of paint. Furthermore, SVK invested in the installation of the most modern paint line in Europe. This technical leap enables SVK to produce slates with an extraordinary high UV-resistance, a super smooth surface where moss doesn't attach and an unequalled paint adhesion.



SUPPORT & TECHNICAL SERVICE

At SVK we have a technical support team at your service to assist on all technical questions you have about the slates They can assist on certification, installation, warranty and much more..



LARGE CAPACITY

We have a production site of 140 Ha in Sint-Niklaas (Belgium). All necessary production facilities are available to organise the complete production of fibre cement slates ourselves.





Benelux
France
Germany
Ireland
United-Kingdom
United-States of
America
Turkey
Poland
Switzerland
Spain
Mexico
Australia
India
Roemenia

BRAND NAME	MONTANA TEXTURED	MONTANA SMOOTH	ARDONIT SMOOTH	ARDONIT TEXTURED
FINISH	Textured surface with dressed edges	Smooth surface with dressed edges	Smooth surface with squared edges	Textured surface with squared edges
SIZE (in mm)	600 X 300 MM 600 X 600 MM	600 X 300 MM 600 X 600 MM	600 X 300 MM 600 X 600 MM	600 X 300 MM 600 X 600 MM
WEIGHT (kg per m² laid)*	20,13 kg	20,13 kg	20,13 kg	20,13 kg
GROSS WEIGHT (kg/ pallet)	1650 kg	1650 kg	1650 kg	1650 kg
N° PER PALLET	1080 pieces	1080 pieces	1080 pieces	1080 pieces
COLOURS	Blue-black (336) & Welsh blue (347)	Blue-black (336)	Blue-black (336) & Premium black (333)	Blue-black (336)
N° SLATES PER M²	13,16	13,16	13,16	13,16
HEADLAP (mm)*	100	100	100	100
BATTEN GAUGE *(mm)	250	250	250	250
BATTENS (m per m²) *	4	4	4	4
RIDGES (90°, 105°, 120°, 135°)	•	•	•	•

*These are data for roof pitches with moderate exposure (< 56,5 l/m² per spell - rafter length ≤ 9 m): standard roof pitch 25°

For following roof pitches please contact SVK for the execution details:

(< 56.5 l/m^2 per spell - rafter length $\leq 9 \text{ m}$): standard roof pitch 22,5° (< 56.5 l/m^2 per spell - rafter length $\leq 6 \text{ m}$): standard roof pitch 25°



INSPIRE AND BE INSPIRED

Discover our website and find the right inspiration for your project. Send us your plans an we will be glad to look at the variety of endless possibilities using SVK slates.





SVK NV

Aerschotstraat 114 9100 Sint-Niklaas P: +44(0)1934 414411 info@svk.be www.svk.be

WWW.SVK.BE

© 2018, SVK nv. The colours printed in this brochure are represented as accurately as possible.SVK may modify the information in this brochure at any time without prior notification. Photography by: Tony Grehan (Ireland) and Jeroen Gijselinckx (Belgium) - SVK06.18/ENG_UK_SLATES_01.1